

MISC. SENSORS

Name: Voltage Sensor, Positive Part #: 37-91165 Range: 0.0-20.00 Units: Volts Type: $y = ax + b$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.00</td> </tr> <tr> <td>4021</td> <td>20.00</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	0.00	4021	20.00	Voltage State, Positive 37-91165 0 or 20 State Table with Hold Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.00</td> </tr> <tr> <td>1200</td> <td>1.00</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	0.00	1200	1.00	Voltage State, Ground 37-91166 0 or 20 State Table with Hold Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>1.00</td> </tr> <tr> <td>2000</td> <td>0.00</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	1.00	2000	0.00	Sensor Output Voltage Internal LCU 0.0-5.0 Volts $y = ax + b$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.00</td> </tr> <tr> <td>4095</td> <td>5.00</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	0.00	4095	5.00																																								
<u>Bits</u>	<u>Value</u>																																																																		
0	0.00																																																																		
4021	20.00																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	0.00																																																																		
1200	1.00																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	1.00																																																																		
2000	0.00																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	0.00																																																																		
4095	5.00																																																																		
Name: LCU Voltage Part #: Internal LCU Range: 0.0-18.0 Units: Volts Type: $y = AX + B$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>0.00</td> </tr> <tr> <td>4095</td> <td>18.00</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	0.00	4095	18.00	LCU Lateral G Internal LCU -8.7 - 8.7 G's $y = AX + B$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-8.70</td> </tr> <tr> <td>4095</td> <td>8.70</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	-8.70	4095	8.70	LCU Horizontal G Internal LCU -8.7 - 8.7 G's $y = AX + B$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>0</td> <td>-8.70</td> </tr> <tr> <td>4095</td> <td>8.70</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	-8.70	4095	8.70																																															
<u>Bits</u>	<u>Value</u>																																																																		
0	0.00																																																																		
4095	18.00																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	-8.70																																																																		
4095	8.70																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	-8.70																																																																		
4095	8.70																																																																		
Name: LCU Box Temp Deg. C Part #: Internal LCU Range: -50-250 Units: Deg C Type: Interpolation Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr><td>0</td><td>220</td></tr> <tr><td>400</td><td>150</td></tr> <tr><td>560</td><td>125</td></tr> <tr><td>720</td><td>105</td></tr> <tr><td>960</td><td>88</td></tr> <tr><td>1280</td><td>70</td></tr> <tr><td>1600</td><td>57</td></tr> <tr><td>1920</td><td>46</td></tr> <tr><td>2240</td><td>34</td></tr> <tr><td>2560</td><td>20</td></tr> <tr><td>2800</td><td>2</td></tr> <tr><td>3300</td><td>-50</td></tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	220	400	150	560	125	720	105	960	88	1280	70	1600	57	1920	46	2240	34	2560	20	2800	2	3300	-50	LCU Box Temp Deg. F Internal LCU -58-428 Deg F Interpolation Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr><td>0</td><td>428</td></tr> <tr><td>400</td><td>302</td></tr> <tr><td>560</td><td>257</td></tr> <tr><td>720</td><td>221</td></tr> <tr><td>960</td><td>190</td></tr> <tr><td>1280</td><td>158</td></tr> <tr><td>1600</td><td>134</td></tr> <tr><td>1920</td><td>114</td></tr> <tr><td>2240</td><td>93</td></tr> <tr><td>2560</td><td>68</td></tr> <tr><td>2800</td><td>36</td></tr> <tr><td>3300</td><td>-58</td></tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	0	428	400	302	560	257	720	221	960	190	1280	158	1600	134	1920	114	2240	93	2560	68	2800	36	3300	-58	String Potentiometer 91123 0-5 Inches $y = ax + b$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>408</td> <td>10</td> </tr> <tr> <td>4044</td> <td>0</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	408	10	4044	0	Linear Potentiometer 91124 0-5 Inches $y = ax + b$ Calibration: <table style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th style="text-align: left;"><u>Bits</u></th> <th style="text-align: left;"><u>Value</u></th> </tr> </thead> <tbody> <tr> <td>1544</td> <td>5</td> </tr> <tr> <td>4092</td> <td>0</td> </tr> </tbody> </table>	<u>Bits</u>	<u>Value</u>	1544	5	4092	0
<u>Bits</u>	<u>Value</u>																																																																		
0	220																																																																		
400	150																																																																		
560	125																																																																		
720	105																																																																		
960	88																																																																		
1280	70																																																																		
1600	57																																																																		
1920	46																																																																		
2240	34																																																																		
2560	20																																																																		
2800	2																																																																		
3300	-50																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
0	428																																																																		
400	302																																																																		
560	257																																																																		
720	221																																																																		
960	190																																																																		
1280	158																																																																		
1600	134																																																																		
1920	114																																																																		
2240	93																																																																		
2560	68																																																																		
2800	36																																																																		
3300	-58																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
408	10																																																																		
4044	0																																																																		
<u>Bits</u>	<u>Value</u>																																																																		
1544	5																																																																		
4092	0																																																																		